




# RC Sample Hose

High performance abrasion resistant, anti static



								
ID		OD		Max W.P.		Burst Pressure		Weight
Dash	Inch	DN	mm	bar	psi	bar	psi	kg/m
32	2	51	77	40	600	120	1800	2.68
40	2.5	63	93.5	40	600	120	1800	3.78
48	3	73	106	40	600	120	1800	4.43

## APPLICATIONS:

Soft wall hose for use of transfer of bulk abrasive materials, particularly with RC Drill rigs

## SERVICE TEMPERATURE RANGE:

-40°C to 70°C

## TUBE:

Black, smooth, antistatic SBR/NR rubber, abrasion resistant, 8mm thick.

## REINFORCEMENT:

High strength synthetic cord

## COVER:

Black, smooth (wrapped finish), antistatic SBR/NR rubber, abrasion resistant

## Standards:

Abrasion loss of the tube according to ISO 4649: 70 +/- 5mm<sup>3</sup>

## HDS Hoses Australia

Midvale, Western Australia

Tel: +61 89274 0020 Fax: +61 89274 6134

[admin@HDS-Hoses.com](mailto:admin@HDS-Hoses.com)

[www.HDS-Hoses.com](http://www.HDS-Hoses.com)



Certificate No.: 73Q14710

RC Drill V2.0