

# Slim Hole Rotary Hose

Oilfield Hose



<b>ID</b>	<b>OD</b>	<b>Max W.P.</b>	<b>Burst Pressure</b>	<b>Bend Radius</b>	<b>Weight</b>

Medium - High Pressure									
Dash	Inch	DN	mm	bar	psi	bar	psi	mm	kg/m
32	2	51	66.8	207	3000	517.5	7500	635	4.40
40	2.5	63	85.9	172	2500	430	6250	762	5.38
48	3	76	99.1	138	2000	345	5000	914	7.05
64	4	102	128.5	103	1500	257.5	3750	1219	10.76

High Pressure									
Dash	Inch	DN	mm	bar	psi	bar	psi	mm	kg/m
16	1	25	38.9	345	5000	862.5	12500	305	2.23
20	1.25	31	50	345	5000	862.5	12500	419	3.97
24	1.5	38	57.4	345	5000	862.5	12500	508	4.95
32	2	51	71.1	345	5000	862.5	12500	635	7.38

## APPLICATIONS:

Designed for use on workover rigs, slim hole or seismograph rigs and small or medium size drilling rigs. Suitable for water well operations, water well core drill, blast or shot hole operations. For conveying drilling mud or air.

## SERVICE TEMPERATURE RANGE:

-40°C to + 82°C

## TUBE:

Black Nitrile Rubber

## REINFORCEMENT:

High Tensile Steel Wire

## COVER:

Perforated Neoprene, Black

## STANDARDS:

Cover meets MSHA 30 CFR 18.65 (flame resistant)

## FITTINGS:

NPT and API threads, Hammer union tails, others on request.

## HDS Hoses Australia

Midvale, Western Australia

Tel: +61 89274 0020 Fax: +61 89274 6134

[admin@HDS-Hoses.com](mailto:admin@HDS-Hoses.com)

[www.HDS-Hoses.com](http://www.HDS-Hoses.com)



Certificate No.: 73Q14710

Slim Hole V1.0